



US009636963B2

(12) **United States Patent**  
**Smith et al.**

(10) **Patent No.:** **US 9,636,963 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **FLUID SPRING AND RUBBER SPRING ASSEMBLY**

(71) Applicant: **Firestone Industrial Products Company, LLC**, Indianapolis, IN (US)

(72) Inventors: **Jason B. Smith**, Avon, IN (US); **David D. Jackson**, Noblesville, IN (US)

(73) Assignee: **Firestone Industrial Products Company, LLC**, Indianapolis, IN (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 38 days.

(21) Appl. No.: **14/404,296**

(22) PCT Filed: **May 29, 2013**

(86) PCT No.: **PCT/US2013/043166**

§ 371 (c)(1),

(2) Date: **Nov. 26, 2014**

(87) PCT Pub. No.: **WO2013/181282**

PCT Pub. Date: **Dec. 5, 2013**

(65) **Prior Publication Data**

US 2015/0165853 A1 Jun. 18, 2015

**Related U.S. Application Data**

(60) Provisional application No. 61/652,412, filed on May 29, 2012.

(51) **Int. Cl.**  
**B60G 11/62** (2006.01)  
**B61F 5/30** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **B60G 11/62** (2013.01); **B61F 5/305** (2013.01); **B61F 5/307** (2013.01); **F16F 9/057** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... B60G 11/62; B60G 2202/152; B60G 2202/143; B60G 11/27; B60G 2206/424;  
(Continued)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,707,045 A \* 1/1998 Easter ..... B60G 17/01933  
188/1.11 E  
6,386,525 B1 \* 5/2002 Stuart ..... F16F 9/052  
267/64.22

**FOREIGN PATENT DOCUMENTS**

EP 1726505 11/2006  
EP 2251562 11/2010  
(Continued)

**OTHER PUBLICATIONS**

International Search Report and Written Opinion for corresponding patent application No. PCT/US2013/043166.

*Primary Examiner* — Mark Lee

(74) *Attorney, Agent, or Firm* — Thomas R. Kingsbury;  
Fay Sharpe LLP

(57) **ABSTRACT**

An end member assembly (204; 404) that is dimensioned for use in forming a gas spring assembly (200; 400) can include an end member body (248; 448) that is dimensioned for securement to a flexible spring member (206; 406) of the gas spring assembly (200; 400). The end member assembly (204; 404) can also include a compliant support structure (250; 450) that is operatively connected to the end member body (248; 448) to support the end member body in spaced relation to an associated structural component (SC2). The end member body (248; 448) can include a side wall (256; 456) that extends in overlapping (OL1; OL2) relation with at least a portion of the compliant support structure (250; 450). The end member (204; 404) can also form at least one chamber (296; 508) within the end member body (248; 448)

(Continued)

